



# LACOPAC

## BLACKOUT 20 oz/yd<sup>2</sup>



FLAME RETARDANT



NO CURLING

### APPLICATIONS

- BOTH SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR COMMUNICATION: signage / banners / POS / hanging banners

### PRODUCT PACKAGING

WIDE FORMAT	40" / 54" / 122"	Rolls of: 98' (30 lm)
SUPER WIDE FORMAT	122"	Rolls of: 197' (60 lm)

### PRODUCT CHARACTERISTICS

WEIGHT	20 oz/yd <sup>2</sup> (680 g/m <sup>2</sup> )
BASE CLOTH	High tenacity polyester 550 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin inkjet lacquer Both side
COLOUR	White 7326
THICKNESS	19 mils (0.49 mm)
TRANSLUCENCY XPT 54 199	0 %
TENSILE STRENGTH NF EN ISO 1421	205 x 171 lbs / inch (180 / 150 daN)
TEAR STRENGTH DIN 53363	45 x 45 lbs (20 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	0,8 lbs /inch
FIRE RETARDANT	M2 / B1 B-s2-d0 (EN 13 501-1) NFPA 701

Average values +/- 10%



SYSTEM  
LOWICK



Company with management system certified by DNV-GL  
ISO 9001 · ISO 14001



[www.dickson-coatings.com](http://www.dickson-coatings.com)  
[www.evergreen-fabrics.com](http://www.evergreen-fabrics.com)