

LACOPAC

BLACKOUT 680 g/m²



FLAME RETARDANT



NO CURLING

APPLICATIONS

- BOTH SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR COMMUNICATION: signage / banners / POS / hanging banners

PRODUCT PACKAGING

WIDE FORMAT	1.02m / 1.37m 3.10m	Rolls of: 30 lm
SUPER WIDE FORMAT	3.10 m	Rolls of: 60 lm

PRODUCT CHARACTERISTICS

WEIGHT	680 g/m ²
BASE CLOTH	High tenacity polyester 550 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer Both side
COLOUR	White 7326
THICKNESS	0.49 mm
TRANSLUCENCY XPT 54 199	0 %
TENSIBLE STRENGTH NF EN ISO 1421	180 / 150 daN
TEAR STRENGTH DIN 53363	20 / 20 daN
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	7 daN / 5cm
FIRE RETARDENT	M2 / B1 B-s2-d0 (EN 13 501-1) NFPA 701

Average values +/- 10%



SYSTEM
LOWICK

