



JET 400

FRONTLIT 11 oz/yd²



NO CURLING

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: banners / signage / POS / pole banners

PRODUCT PACKAGING

WIDE FORMAT	42"	Rolls of: 164' (50 lm)
SUPER WIDE FORMAT	126"	Rolls of: 164' (50 lm) and 328' (100 lm)

PRODUCT CHARACTERISTICS

WEIGHT	11 oz/yd ² (370 g/m ²)
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer One side
COLOUR	White 7325
THICKNESS	13 mils (0.34 mm)
TRANSLUCENCY XPT 54 199	15 %
TENSILE STRENGTH NF EN ISO 1421	240 x 228 lbs / inch (210 / 200 daN)
TEAR STRENGTH DIN 53363	56 x 45 lbs (25 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	0,8 lbs /inch
FIRE RETARDENT	-

Average values +/- 10%



SYSTEM
LOWICK



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001



www.dickson-coatings.com
www.evergreen-fabrics.com