



# JET 530

## FRONTLIT 17 oz/yd<sup>2</sup>



FLAME RETARDANT

### APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: banners / signage / POS / indoor advertising

### PRODUCT PACKAGING

WIDE FORMAT	42" / 54" / 64"	Rolls of: 98' (30 lm)
SUPER WIDE FORMAT	126"	Rolls of: 197' (60 lm)

### PRODUCT CHARACTERISTICS

WEIGHT	17 oz/yd <sup>2</sup> (560 g/m <sup>2</sup> )
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer One side
COLOUR	White 7325
THICKNESS	19 mils (0.47 mm)
TRANSLUCENCY XPT 54 199	6 %
TENSILE STRENGTH NF EN ISO 1421	240 x 228 lbs / inch (210 / 200 daN)
TEAR STRENGTH DIN 53363	56 x 45 lbs (25 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	0,8 lbs /inch
FIRE RETARDENT	M2 / B1

Average values +/- 10%



SYSTEM  
LOWICK



Company with management system certified by DNV-GL  
ISO 9001 · ISO 14001



[www.dickson-coatings.com](http://www.dickson-coatings.com)  
[www.evergreen-fabrics.com](http://www.evergreen-fabrics.com)